








Ingress Disc

- · ngress Discs are used as a means of maintaining the integrity of the enclosure prior to the availability of the cable. They can be used to exclude dust and moisture from entering the enclosure, enabling the Cable Gland to be installed prior to the cable.
- Ingress Discs are available for all types of Cable Glands used in industrial and Ex e applications and are produced in high quality nickel plated brass with an Ingress protection rating of IP66 when the sealing ring is engaged finger tight and one spanner turn



| Cable Gland Size | Cable Gland Type | |
|------------------|------------------------------|---------------------------------------|
| | Inner Sealing Washer for A2F | Outer Sealing Washer for E & C Series |
| 2Os16 | A2FID-2Os16 | CWID-2Os16 |
| 2Os | A2FID-2Os | CWID-2Os |
| 20 | A2FID-2O | CWID-2O |
| 25 | A2FID-25 | CWID-25 |
| 32 | A2FID-32 | CWID-32 |
| 40 | A2FID-4O | CWID-4O |
| 5Os | A2FID-5Os | CWID-5Os |
| 50 | A2FID-5O | CWID-50 |
| 63s | A2FID-63s | CWID-63s |
| 63 | A2FID-63 | CWID-63 |
| 75s | A2FID-75s | CWID-75s |
| 75 | A2FID-75 | CWID-75 |
| 90 | A2FID-9O | CWID-90 |
| 100 | A2FID-100 | CWID-100 |
| 115 | A2FID-115 | CWID-115 |
| 130 | A2FID-13O | CWID-13O |

ORDERING INFORMATION

Discs can be ordered as a separate accessory using the below references or pre-installed in the cable gland by adding '8' to the end of ordering code.